

CI/SfB	(29)	(K2)
CAW P10		
Uniclass JP10:L68114		

## Product Information

### Description

FO100 Putty Pads are an easy to apply fire and sound rated seal supplied as a non-setting putty. The pad is hand workable, re-useable and re-serviceable due to its non-setting properties.

### Usage / Purpose

When electrical sockets and switches are installed in dry lining partitions, the original fire rating of the partition is compromised. Fitting Nullifire FO100 Putty Pads will reinstate the fire rating of the partition for up to two hours (depending on the partition fire rating and design). They will also prevent the passage of smoke and flames in a fire, as well as sound and air movement during service life, through the electrical socket, into the cavity.

Nullifire FO100 Putty Pads are shaped for use on both single and double electrical socket installations in dry lining walls. The pads are supplied in a cross shape for internal installation in a socket.

### Available Sizes

Size (mm)	To Fit
170 x 170	Single socket
230 x 170	Twin socket

### Packaging

20 pieces per box

### Availability

Direct from Tremco CPG UK Limited (see details on this TDS).

## Usage Guidelines

Always read SDS, pre-application guidance and relevant application detail prior to application. Ensure the latest documents are downloaded prior to every project commencement.

### Necessary Tools

Suitable PPE only. No tools required.

### Preparation

- Ensure that all surfaces are clean and free from dust and debris, and that the available pad is the correct size for the installation.
- Ensure power supply is isolated before commencing work.

### Installation

- Remove the backing paper from one side of the pad
- Insert the pad into the socket back box so that the pad completely covers the back and sides.
- Make a slit to allow wiring to pass through the pad.
- Trim back around the box, working around the existing cable exit to ensure continuity.

### Maintenance

No maintenance required after installation. Routine inspection recommended to ensure no damage.

### Storage

Store between +5°C and +25°C in dry conditions. Keep away from sources of ignition.

### Shelf Life

At least 12 months when stored as recommended.

### Health & Safety Precautions

Safety data sheet must be read and understood before use.

**Nullifire**  
Smart Protection

# FO100

## Intuputty Putty Pad



### Key Benefits Summary

- Tested to EN 1366-3:2009, 120 minutes fire resistance in 100 mm and 139 mm dry lining
- Sound insulating BS EN ISO 140-3:1995
- Solvent free (no VOC)
- Ready to use – no special tools required
- Cold smoke seal

CE  
ETA 18/0579



# FO100

## Intuputty Putty Pad

**Nullifire**  
Smart Protection

### Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

### Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.