

TECHNICAL DATASHEET

Introduction:

Firehalt HT Adhesive is a proprietary silicate based refractory adhesive/sealant that is designed to be used with Firehalt barrier products.

After application it will remain tacky for 5 mins and skin over after 10 mins. It will remain flexible at room temperatures and stable at elevated temperatures.

Firehalt HT Adhesive can be used to fill small holes and gaps around pipes and cables.

Above 800°C it sets to form a solid ceramic mass that is resistant to thermal shock.

Physical Properties:

Description:	Lightweight / non-corrosive / User friendly / flexible / durable / easy to apply with standard skeleton gun
Colour:	White
Proprietary Treatment:	Non-corrosive.
Weight:	500g Dispensing Tubes
Shelf Life	1 to 2 years
Storage Temp. Range	Between -5°C to 30°C

Packing Specification & Product Dims:

Cardboard Box	25 tubes / box
---------------	----------------



Culimeta-Saveguard Ltd,
 +44 (0)161 344 2484
 sales@saveguard.com
 www.culimeta-saveguard.com



The information on this Data Sheet is provided in good faith. However, the company reserves the right to alter or update this data as and when additional information is received. Firehalt products should only be fitted in accordance with the guidelines provided by the manufacturer. Any deviations must be authorised by the manufacturer or their representatives.

Issue No:	1	Page:	1 of 1	Dated:	1 May 2017	File Ref:	firehalt ht adhesive	.pdf
-----------	---	-------	--------	--------	------------	-----------	----------------------	------