



Product Number: 64

Woodfiller

This product is a water-based general purpose wood filler. It can withstand temperatures up to 1000°C

PHYSICAL DATA:

| | |
|-------------------|-------------|
| Type: | Water-based |
| Colour: | Natural |
| Viscosity: | Paste |
| Specific Gravity: | 1.40 |

RECOMMENDATION FOR USE:

| | |
|--------------------------------|---|
| Application methods: | Putty Knife or paint scraper |
| Conditions during application: | Temperature of air and substrate must be above 5 °C. |
| Drying time: | Variable depending on thickness and ambient conditions. |
| Coverage: | 100ml per 140 grams |

MISCELLANEOUS:

| | |
|---------------------|---|
| Size of containers: | 250ml, 500ml and 1 litre |
| Remarks: | Frost-free freight and storage. STIR WELL before use |
| Shelf Life: | 12 months in unopened original packaging (Stored between 5-30 °C) |

DIRECTIONS FOR USE:

It is advisable to wear gloves, although the Woodfiller is non-toxic, safe handling practices should still be implemented to avoid irritating sensitive skin.

If glue makes contact with eyes, flush thoroughly with water for at least 15 minutes.

Seek medical attention. For skin wash with soap and water.

The surface must be clean, free from all loose materials, dust, dirt, oil and any other contaminants.

Apply with a putty knife or paint scraper by pasting over the hole or crack.

For deep holes apply Woodfiller in several layers, allowing each layer to dry between applications.

Larger applications may shrink and crack on drying. Re-apply Woodfiller.

Clean tools with water.