

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 1

Compilation date: 7//06/2012

Sent to: TW Consulting Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Product code: SFR -D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: An air drying water borne flame retardant coating for use on surfaces within buildings.

apply by brush, roller or spray

1.3. Details of the supplier of the safety data sheet

Company name: Thermoguard UK Ltd

3, Kirkby Street

Hull

HU2 0HE

United Kingdom

Tel: 01142 768 008

Fax: 01624 825 526

Email: sales@thermoguard.co.uk

1.4. Emergency telephone number

Emergency tel: 01624 825 115

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Symbol not required.

Safety phrases: S2: Keep out of the reach of children.

S7: Keep container tightly closed.

S20/21: When using do not eat, drink or smoke.

S24/25: Avoid contact with skin and eyes.

S27/28: After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of soap and water or proprietary skin cleaner.

S29/35: Do not empty into drains; dispose of this material and its container in a safe

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 2

way.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection. S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Safety data sheet available for professional user on request.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ZINC BORATE - REACH registered number(s): 01-2119691658-19-0001

EINECS	CAS	CHIP Classification	CLP Classification	Percent		
235-804-2	138265-88-0	N: R50	Aquatic Acute 1: H400	1-10%		
PROPANE DIOL - REACH registered number(s): 01-2119456809-23-0003						

200-338-0	57-55-6	Substance with a Community	-	1-10%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Do NOT use solvent or thinners

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If unconscious, check for breathing

and apply artificial respiration if necessary. If unconscious and breathing is OK, place in

the recovery position. Consult a doctor.

Inhalation: Remove to fresh air Keep the patient warm and at rest If unconscious and breathing is

OK, place in the recovery position. If unconscious, check for breathing and apply artificial

respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact. repeated exposure may cause skin

dryness and/or cracking

Eye contact: There may be irritation and redness.

Ingestion: No data available. **Inhalation:** No data available.

Delayed / immediate effects: No data available.

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In all cases of doubt,or when symptoms persist seek medical attention. Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: extinguish with foam,dry powder,carbon dioxide or water fog Suitable extinguishing

media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes. Do not allow run off to enter watercourses or drains

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid. Avoid breathing any vapours

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in

the air. Avoid skin and eye contact Smoking , eating and drinking should be prohibited in

mixing and application area Do not allow to enter drains or watercourses

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. store between 5 and 30oC in a dry well ventilated area

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): the identified uses of this product are detailed in section 1

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ZINC BORATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	10 mg/m3	-	-	-

PROPANE DIOL

UK	150 ppm	-	-	_
-				

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place. Ensure

there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection must be used if the general level exceeds the recommended

occupational exposure limit

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place. Prevent

from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: VariousOdour: Characteristic odour

Solubility in water: Miscible

Viscosity: Viscous

Kinematic viscosity: 1-2 poise

Viscosity test method: Cone & plate @ 20 oC

Boiling point/range°C: 100 Flammability limits %: lower: not flammable

Flash point°C: not relevant Relative density: 1.3 - 1.4

pH: 8.5 - 9.0 VOC g/l: 30 grammes/litre maximum

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 5

9.2. Other information

Other information: VOC Content: EU limit for this product is(CatA/i) is 500 g/litre

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions. In a Fire, hazardous

composition products may be produced

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ZINC BORATE

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	4H LC50	0.002	g/l
ORAL	RAT	LD50	3500	mg/kg

PROPANE DIOL

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>20,000	mg/kg
VAPOURS	RBT	1H LC50	317.4	mg/l

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact. repeated exposure may cause skin

dryness and/or cracking

Eye contact: There may be irritation and redness.

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 6

Ingestion: No data available.
Inhalation: No data available.
Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of waste and residues according to local authority requirements

Waste code number: 08 01 12

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: not classified

14.2. UN proper shipping name

Shipping name: not classified

14.3. Transport hazard class(es)

Transport class: not classified (not+classified)

14.4. Packing group

Packing group: not classified

THERMOGUARD SFR DUALCOAT (SMOKE & FLAME RETARDANT) - GENERAL

Page: 7

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: Always transport in upright sealed containers Ensure that persons transporting the

product what to do in the event of an accident or spillage

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: not Relevant

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H400: Very toxic to aquatic life.

R50: Very toxic to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.