

Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: Nullifire TS134 A

· MSDS code: W-N-TS134A

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Coatings Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

Nullifire

Torrington Avenue, Coventry, CV4 9TJ

T: +44 (0) 2476855000, F: +44 (0) 2476469547

www.nullifire.com, protect@nullifire.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 2476855000. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Contains:

cristobalite, crystalline

· Hazard statements

H226 Flammable liquid and vapour.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 1)

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P260 Do not breathe mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection. P280

Get medical advice/attention if you feel unwell. P314

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Supplemental information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:				
CAS: 14464-46-1 EINECS: 238-455-4	cristobalite, crystalline STOT RE 1, H372	30- <50%		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10- <20%		
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5- <10%		
CAS: 25190-06-1	Polytetrahydrofuran Aquatic Chronic 3, H412	5- <10%		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5- <10%		
CAS: 123-54-6 EINECS: 204-634-0	pentane-2,4-dione Flam. Liq. 3, H226; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	1- <5%		
CAS: 41556-26-7 EINECS: 255-437-1	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	0.1- <1%		

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down. Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Danger of serious damage to health by prolonged exposure.

Irritating to eyes and skin.

Vapours have narcotic effect.

Repeated exposure may cause skin dryness or cracking.

Allergic reactions

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

Additional information:

The lists valid during the making were used as basis.

(Contd. on page 5)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 4)

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Avoid breathing vapours.

· Respiratory protection:

Use only in well-ventilated areas.

Only during spraying without adequate removal by suction.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A1/P3

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Rubber gloves

Plastic gloves

EN 374

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: According to product specification

· Odour: Solvent-like

(Contd. on page 6)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

	(Contd. of page 5)	
Odour threshold:Boiling point/Boiling range:	Not determined. Undetermined.	
· Flash point:	32 °C	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Density at 20 °C:	1.33 g/cm³	
· Solubility in / Miscibility with water: Not miscible or difficult to mix.		
Solvent content: VOC (EU) 9.2 Other information	300 g/l (mixed, A + B) No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- · 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:				
1330-20	1330-20-7 xylene (mix)			
Oral	LD50	4300 mg/kg (rat)		
Dermal	LD50	2000 mg/kg (rabbit)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Irritating effect.

Repeated exposure may cause skin dryness or cracking.

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause allergic skin disorders in sensitive individuals.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 6)

· STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1330-20-7 xylene (mix)

EC50/48 h 7.4 mg/L (daphnia magna)

EC50/72 h | 10 mg/L (skelettonema costatum)

LC50/96 h 3.77 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

May cause long lasting harmful effects to aquatic life.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

· Waste disposal key: UK: HP3 HP5 HP14

European waste catalogue 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances 15 01 10* packaging containing residues of or contaminated by dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 8)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 7)

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14:	Transport	information
-------------	-----------	-------------

· 14.1 UN-Number

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR **1263 PAINT** · IMDG, IATA **PAINT**

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

Label

· 14.4 Packing group

· ADR, IMDG, IATA Ш

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids.

· Danger code (Kemler): 30 · EMS Number: F-E,S-E

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

ml

· Transport category 3

· Tunnel restriction code D/E

(Contd. on page 9)



Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

(Contd. of page 8)

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L Code: E1

JOGE: ET

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

ml

· UN "Model Regulation": UN 1263 PAINT, , III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)



(Contd. of page 9)

Printing date 18.09.2015 Version number 1 Revision: 18.09.2015

Trade name: Nullifire TS134 A

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3