



FIRE RESISTANT AQUASTEEL WB+

EGGSHELL FINISH

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Zeroflame AquaSteel WB+ Eggshell Finish is a hard wearing decorative finish for application over Zeroflame AquaSteel WB+ Intumescent Coating.

APPEARANCE

Zeroflame AquaSteel WB+ Eggshell Finish is an eggshell finish. BS4800, RAL and NCS colours available on request.

COVERAGE RATES

12m²/litre per coat. Over Zeroflame AquaSteel WB+ Intumescent Coating one coat is normally sufficient but for dark contrasting colours two may be required.

PRODUCT SPECIFICATION

VOC: Max. 30 g/litre (conforms to European maximum of 140 g/litre.)

GENERAL SAFETY

- Ensure good ventilation during application and drying.
- In case of insufficient ventilation, wear suitable respiratory equipment.
- Use personal protective equipment as required.
- After contact with skin, wash gently with plenty of soap and water.
- In case of contact with eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Keep out of reach of children.
- When not in use keep containers tightly closed.

SURFACE PREPARATION

Ensure that the product to be coated is even and fully dry.
Ensure the surface to be painted is sound, clean, dry and free from grease or any substance liable to give adhesion problems. Scrape off any old or flaking paint until you have a firm well adhered surface; if in doubt remove all existing coatings. For existing gloss and eggshell finishes wet abrade and rinse with clean water to remove any residues.

Zeroflame AquaSteel WB+ Eggshell Finish is designed as a colour finish for Zeroflame AquaSteel WB+ Intumescent Coating.

SITE CONDITIONS DURING APPLICATION

Throughout the period of application and drying the ambient and substrate temperature should be between 5-30°C with ambient relative humidity below 75%.

APPLICATION METHODS

Stir well before use. Apply by brush or roller. Zeroflame AquaSteel WB+ Eggshell Finish must not be thinned. Coverage rates must be adhered to in order to achieve the fire rating.

DRYING TIME

4 hours at 20°C per coat. Allow to dry for a minimum of 4 hours at 20°C between coats.

CLEAN UP

Remove as much product from application equipment as possible before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

PACK SIZE

Pack Size: 2.5 litres.

This information is offered in good faith but without guarantee or liability. In cases of doubt, users should consult with relevant authority. Information given herein is supplied for your guidance only and is based upon the results of controlled tests and experience obtained in the application of the product referred to by Decor Ireland. As the supplier only, Decor Ireland has no control over the method or conditions of application of the product and consequently no warranties expressed or implied are intended to be given as to the coverage or performance of the products mentioned or referred to herein and no liability will be excepted for any loss, damage or physical injury from the use or application of the information, data or products mentioned or referred to herein.

Aquasteel and Zeroflame are Trade Marks of Decor Ireland.

STOCKIST INFORMATION

Rawlins Paints | Northspeed House | Moorview | Holbeck | Leeds | LS11 9NF
T: 0113 2455450 / E: sales@rawlinspaints.com
W: www.rawlinspaints.com

Issue Date 01/10/14

Zeroflame AquaSteel WB+ Eggshell Finish Technical Data - Page 2 of 2