

Product Data Sheet



Revision 6 - January 2019








Astro X Series CE Pipewrap UL

Intumescent CE Pipe Wrap UL 25m

- CE Marked.
- Certifire Approved.
- Tested on a wide range of plastic pipes PVC, PP, HDPE & PE Pipes.
- Tested in accordance with EN 1366-3: 2009.
- Classified in accordance with EN 13501-2.
- Supplied on a roll cut to size on site.





Product Description

Astro X Series CE Pipe Wrap UL is designed and tested to seal service penetration apertures containing plastic and metallic pipes, pipes with insulation, using thermoplastic composites based on graphite Intumescent technology.

Developed to provide a high volume expansion and pressure seal during a fire. The Astro X Series CE Pipe Wrap UL offers EI120 tested to EN1366-3, the maximum diameter being 200mm, the ultra thin design of Astro X Series CE Pipe Wrap UL ensuring that they can be installed in to the tightest of locations.

Astro X Series CE Pipe Wrap UL can be installed in flexible wall, rigid wall, rigid floor constructions and in Batt seals. They are compatible with polypropylene (PP), polyethylene (PE) and polyvinyl chloride (PVC) pipes. Astro X Series CE Pipe Wrap UL is tested with end capping configurations that cover U/C & C/C pipes.

Supplied in 25m rolls or cut to size.



Astroflame Fireseals Ltd Unit 8 I.O Centre Stephenson Road Segensworth, Fareham Hampshire, PO15 5RU 15 1121-CPR- JA5083

ETA - 15/0618
ETAG 026-Part 1
ETAG 026-Part 2
ASTRO X SERIES CE PIPE
WRAP UL
" See ETA - 15/0618 for
Relevant characteristics



Product Description

Astro X Series CE Pipe Wrap UL is installed around combustible pipes to form a penetration seal used to reinstate the fire resistance performance of wall and floor constructions, where they have been provided with apertures for the penetration of combustible pipe services.

Astro X Series CE Pipe Wrap UL is installed around the pipe at the soffit and upper face of floors and both faces of walls, depending on application and by applying a number of passes to reach the required thickness.

Outer Pipe Dia	No. Wraps	Thickness
32mm	1	2mm
40mm	1	2mm
55mm	2	4mm
63mm	2	4mm
75mm	2	4mm
82mm	2	4mm
90mm	3	6mm
110mm	3	6mm
125mm	4	8mm
160mm	4	8mm
200mm	5	10mm

Product Availability

Product Code	Product Description	Size
AFIPWELX/CE	Astro X-Series CE Pipe Wrap UL	25m

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Size Typical example:- 10 / AFIPWELX/CE / Astro X-Series CE Pipe Wrap UL / 25m

>> Tel: <u>01329 844 500</u> or >> Email: <u>sales@astroflame.com</u>

Installation

Please see (TDS) Technical Data sheet - This can be requested from our sales team T: <u>01329 844 500</u> or E: <u>sales@astroflame.com</u>

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: <u>01329 844 500</u> or E: <u>sales@astroflame.com</u>

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.